

ENGINE DRIVEN

4 and 5-Stage High Pressure Breathing Air Compressors

- › **Pressure**
up to 6000 psig
up to 414 bar
- › **Charging Rate**
13 to 60 scfm
368 to 1700 l/min
- › **Power**
13.5 to 60 hp
10 to 45 kW



The ENGINE DRIVEN compressor for recharging SCBA or SCUBA cylinders combines compressor, purification system and engine drive.

The frame's rugged design is specific to the requirements of the engine drive/compressor block assembly.

Engine Driven

STANDARD SCOPE OF SUPPLY

- BAUER breathing air purification system
- BAUER PLC based controller with four line text display
- NEMA 4 rated electrical enclosure with **UL**® listed control panel with hourmeter
- Compressor low oil pressure and high temperature safety shutdowns
- Automatic condensate drain system with non-corrosive condensate reservoir and integrated float switch. Automatic "Full" indication and compressor shutdown
- Interstage pressure gauges
- Electric start package including electric clutch and speed control solenoid

AVAILABLE ACCESSORIES (factory installed)

- Audible alarms for safety shutdowns
- CO monitor
- Other accessories available on request

Diesel Drive Models

- Closed loop water cooled diesel

DIMENSIONS L x W x H inches (mm)

- H13-K26 63 x 49 x 46 (1600 x 1245 x 1168)
- H35-K42 95 x 52 x 49 (2413 x 1320 x 1245)
- K60 112 x 52 x 53 (2845 x 1320 x 1346)

WEIGHT pounds (kg)

- 1300 - 3750 (590 - 1700)

Technical Data

Model	Charging rate ¹⁾		Number of stages	Motor		FAD ²⁾	RPM	Purification system
	scfm	l/min		hp	kW			
5000 psig (345 bar)								
K20-G	21	595	4	20	15	17.5	1300	P5
K20-D	^	^	^	27	20	^	^	^
K26-D	26.4	748	^	^	^	22	1350	^
K42-D	42	1190	^	44	33	35	1300	P10
K60-D	60	1700	^	60	45	50	1350	P12 SECURUS
6000 psig (414 bar)								
H13-G	13	368	4	13.5	10	10.8	1420	P2 SECURUS
H13-D	^	^	^	18	13	^	^	^
H19-D	19.2	544	5	27	20	16	1050	P5 SECURUS
H25-D	25.2	714	^	^	^	21	1300	^
H35-D	35.9	1017	4	44	33	29.8	1200	P10 SECURUS

1) Based on recharging an 80 cubic foot tank from 500 to 3000 psig.

2) Compressor capacity referenced to standard inlet conditions.

G = Gasoline engine drive D = Diesel engine drive Alternate drives available.

Dimensions and weight are approximate and are subject to change.

Brownie's Marine Group

940 NW 1st Street | Fort Lauderdale, FL 33311

Ph. +1 (954) 462-5570

Fax +1 (954) 462-6115

info@browniesmarinegroup.com